



bibcop: L^AT_EX Package for Style Checking of **.bib** Files*

Yegor Bugayenko
yegor256@gmail.com

2026-08-17, 0.0.34

NB! The T_EX processor must be invoked with the `--shell-escape` option, and [Perl](#) must be installed on the system. This package does not operate on Windows.

1 Introduction

This package scans a **.bib** file for stylistic errors and emits warning messages whenever issues are detected (the package must be included before all other bibliography-related packages):

```
\documentclass{article}
\usepackage{bibcop}
\begin{document}
\bibliographystyle{plain}
\bibliography{main}
\end{document}
```

Warnings, if any, appear in the T_EX log. Once the issues in the **main.bib** file have been resolved, the warnings cease.

Bibcop is largely indifferent to the formatting of the **.bib** file. It does not emit warnings when a comma is omitted after the final tag of a BibT_EX entry, nor when the tags and their equals symbols are misaligned. Bibcop's attention is reserved for the content of the tags and the inconsistencies that may arise within them.

Whenever the **.sty** file is used directly (without installation into the T_EX tree), the **bibcop.pl** file must accompany it—it is the Perl script that performs the actual checking of **.bib** files. The **.sty** serves merely as a thin wrapper around it.

The `\usepackage{bibcop}` declaration must immediately follow `\usepackage{biblatex}` (whenever BibL^AT_EX is in use); otherwise no warnings will be issued by bibcop.

*The sources are in GitHub at [yegor256/bibcop](https://github.com/yegor256/bibcop)

2 Package Options

The behaviour of the package may be configured by means of several package options:

verbose The **verbose** package option prints all debugging messages to the $\text{\TeX}$ log:

```
\usepackage[verbose]{bibcop}
```

script The package relies upon the `bibcop.pl` file, a Perl script that performs all of the work. This file is expected to reside either in the current directory or within the `texmf-dist/scripts/bibcop/` directory. By means of the **script** option, the location of the script may be specified explicitly (the option is not recommended unless a particular need arises):

```
\usepackage[script=my-perl-script.pl]{bibcop}
```

no* Specific rules may be suppressed by means of one of the **no*** package options:

```
\usepackage[nodoi,nowraps]{bibcop}
```

The following options are available:

- **nocaps** allows arbitrary capitalization in titles;
- **nowraps** allows titles to have no double curly braces;
- **nodoi** allows the absence of the `doi` tag in all entries;
- **noinproc** allows the `booktitle` tag in `@inproceedings` entries to not start with “Proceedings of the”;
- **noorg** allows mentioning of ACM/IEEE in the `booktitle` tag;
- **notags** allows any tags and allows missing important tags.

3 The Rules

The following constitutes a substantially complete enumeration of the rules enforced on a `.bib` file:

types Only the `@article`, `@book`, `@inproceedings`, `@phdthesis`, `@incollection`, and `@misc` types of $\text{BIB}\text{\TeX}$ entries are admitted. All other types, such as `@manual`, `@inbook`, and [many others](#), are forbidden. The aforementioned six suffice for every conceivable purpose.

tags Each type of $\text{BIB}\text{\TeX}$ entry has a tightly constrained list of admissible tags. Tags absent from the list are forbidden.

doi Every $\text{BIB}\text{\TeX}$ entry must contain a `doi` tag, namely the unique [Digital Object Identifier](#) of the cited material. To forestall ambiguity, it is sound practice to record the DOI in every case. The [doi](#) package is likewise recommended, as it converts all “doi” fields into hyperlinks.

caps Within the `title`, `booktitle`, and `journal` tags, every major word must be capitalised, as [recommended](#) by the APA:

```
title = {A Preliminary Architecture for a Basic Data-Flow Processor}
```

Here, the leading “A” is capitalised because it opens the title. The word “for” and the article “a” are minor words and therefore appear in lower case. Both components of the composite word “Data-Flow” are capitalised. This rule may occasionally be relaxed where a custom capitalisation is preserved as imposed by the author of the paper. In such cases, the words bearing custom capitalisation must be enclosed in curly brackets, for example:

```
title = {Structured Programming {with} Go {To} Statements}
```

This rule may be disabled by means of the `nocaps` package option.

author The `author` field must contain a list of authors separated by “and”. Each author must comprise two components separated by a comma: the first denotes the surname of the author, the second a list of given names separated by spaces, for example:

```
author = {Knuth, Donald E. and Duane, Bibby}
```

Where the list of authors is exceedingly long, “and others” may be employed:

```
author = {Knuth, Donald E. and others}
```

Whenever given names are abbreviated to a single letter, a trailing full stop is required. An author name with bespoke formatting may be enclosed in curly brackets, whereupon Bibcop disregards it:

```
author = {{Some author} and {I}}
```

shorts Abbreviation of words is permitted only within the `author` tag; the following, for instance, is impermissible:

```
journal = {J. Log. Compute}
```

It must instead be replaced by the following:

```
journal = {Journal of Logic and Computation}
```

brackets The `title`, `booktitle`, and `journal` fields must be enclosed in double brackets, for example:

```
title = {{A Survey of Symbolic Execution Techniques}}
```

This is necessary in order to prevent the down-casing of capitalised words, which certain bibliography styles otherwise perform.

year The year may not appear within the title of a conference or a journal; the following, for instance, is impermissible:

```
booktitle = {{1994 IEEE International Conference on Computer Languages}},
```

The year is to be recorded solely within the `year` tag, and nowhere else. Within the `year` tag, only numerals are admissible:

```
year = {1994},
```

month The `month` field may contain only a numeral:

```
month = {12},
```

volume The **volume** field may contain only a numeral:

```
volume = {32},
```

number The **number** field may contain only a numeral:

```
number = {132},
```

pages The **pages** field may contain either a single numeral or two numerals separated by a double dash:

```
pages = {145--163},
```

proceedings The **booktitle** within an **@inproceedings** entry must invariably begin with “Proceedings of the”, as illustrated below:

```
booktitle = {{Proceedings of the International
              Conference on Computer Languages}},
```

This rule may be disabled by means of the **noinproc** package option.

arXiv Whenever **archivePrefix** is present, **eprint** and **primaryClass** must likewise be present and must conform to the formatting principles of [arXiv identifiers](#):

```
@misc{bugayenko2021,
      archivePrefix = {arXiv},
      eprint = {2111.13384},
      primaryClass = {cs.PL},
}
```

typography All tags within each **BIB_TEX** entry are inspected for compliance with elementary typographic conventions:

- No space is admissible before a comma, semicolon, colon, full stop, question mark, or exclamation mark;
- Text may not terminate in a full stop, comma, semicolon, colon, or dash;
- A triple dash must be flanked on both sides by spaces.

Unicode Non-ASCII characters are prohibited throughout the **.bib** file, unless curled brackets protect them:

```
@book{proust1913,
      author = {{Proust, Marcel}},
      title = {{À la Recherche du Temps Perdu}},
      publisher = {{Éditions Grasset}},
}
```

The brackets that delimit the value of a tag protect nothing, which is why one extra pair is required around the text itself (and yet one more around a **title**, since it demands its own pair anyway). This is how a bibliography in Cyrillic, Greek, Arabic, or Chinese may be kept, even though transliteration into Latin remains the safer choice.

4 Implementation

First, we include a few packages. We need [iexec](#) for executing Perl scripts:

```

1 \RequirePackage{iexec}
   Then, we process package options:
2 \RequirePackage{pgfopts}
3 \pgfkeys{
4   /bibcop/.cd,
5   notags/.store in=\bibcop@notags,
6   noorg/.store in=\bibcop@noorg,
7   noinproc/.store in=\bibcop@noinproc,
8   nocaps/.store in=\bibcop@nocaps,
9   nodoi/.store in=\bibcop@nodoi,
10  nowraps/.store in=\bibcop@nowraps,
11  verbose/.store in=\bibcop@verbose,
12  script/.store in = \bibcop@script,
13 }
14 \ProcessPgfPackageOptions{/bibcop}

```

`bibcop.pl` Then, we find the Perl script:

```

15 \makeatletter
16 \ifdefined\bibcop@script\else
17   \IfFileExists{bibcop.pl}
18     {\gdef\bibcop@script{perl ./bibcop.pl}}
19     {\gdef\bibcop@script{bibcop}}
20 \fi
21 \message{bibcop: The Perl script is at '\bibcop@script'^J}%
22 \makeatother

```

`\bibcop@exec` Then, we define a supplementary command to execute the Perl script:

```

23 \RequirePackage{shellesc}
24 \makeatletter
25 \newcommand\bibcop@exec[1]{
26   \iexec[maybe]{\bibcop@script\space
27     \ifdefined\bibcop@verbose--verbose\fi\space
28     \ifdefined\bibcop@notags--no:tags\fi\space
29     \ifdefined\bibcop@noorg--no:org\fi\space
30     \ifdefined\bibcop@noinproc--no:inproc\fi\space
31     \ifdefined\bibcop@nodoi--no:doi\fi\space
32     \ifdefined\bibcop@nocaps--no:caps\fi\space
33     \ifdefined\bibcop@nowraps--no:wraps\fi\space
34     --latex '#1'}%
35   \message{bibcop: style checking finished for #1^^J}%
36 }
37 \makeatother
38
39 % \begin{macro}{\bibliography}
40 % Then, we re-define the |\bibliography| command:
41 %   \begin{macrocode}
42 \makeatletter
43 \ifdefined\bibliography
44   \let\bibcop@oldbibliography\bibliography
45   \renewcommand\bibliography[1]{%

```

```

46     \bibcop@exec{#1.bib}%
47     \bibcop@oldbibliography{#1}%
48   }
49 \fi
50 \makeatother

```

\addbibresource Then, we re-define the \addbibresource command:

```

51 \makeatletter
52 \ifdefined\addbibresource
53   \let\bibcop@oldaddbibresource\addbibresource
54   \renewcommand\addbibresource[1]{%
55     \bibcop@exec{#1}%
56     \bibcop@oldaddbibresource{#1}%
57   }
58 \fi
59 \makeatother

60 \endinput

```

Change History

0.0.1		more rules added.	5
	General: First draft.	5	0.0.4
0.0.12	General: A few package options introduced to give users an ability to disable certain style rules: nocaps , nowraps , notags , noorg , noinproc , and nodoi . Also, a command line script gets a new set of options, which start from -no: , for example -no: caps	5	0.0.4
		General: Extra checks for the typography, together with more extensive Perl testing.	5
		Package options introduced, the verbose option enables detailed logging inside the T _E X log. . . .	5
		The -verbose option introduced, to enable debugging information only on demand. . .	5
0.0.16	\bibcop@exec : When -shell-escape is not set, there is no validation performed. . . .	5	0.0.6
		General: The script package option introduced, to enable explicit configuration of the location of the bibcop.pl Perl script.	5
0.0.2	General: Documentation extended,		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

A			D		
\addbibresource	...	<u>51</u>	\doi		<i>2</i>
\arXiv		<i>4</i>	E		
\author		<i>3</i>	\endinput		<i>60</i>
B			G		
\begin		<i>39, 41</i>	\gdef		<i>18, 19</i>
\bibcop.pl		<u>15</u>	I		
\bibcop@exec		<i>23, 55</i>	\iexec		<i>26</i>
\bibcop@nocaps		<i>8, 32</i>	\ifdefined		
\bibcop@nodoi		<i>9, 31</i>			<i>16, 27, 28, 29,</i>
\bibcop@noinproc	..	<i>7, 30</i>			<i>30, 31, 32, 33, 43, 52</i>
\bibcop@noorg		<i>6, 29</i>	\IfFileExists		<i>17</i>
\bibcop@notags		<i>5, 28</i>	M		
\bibcop@nowraps	..	<i>10, 33</i>	\makeatletter		
\bibcop@oldaddbibresource		<i>53, 56</i>			<i>15, 24, 42, 51</i>
\bibcop@oldbibliography		<i>44, 47</i>	\makeatother		
\bibcop@script	..	<i>12,</i>			<i>22, 37, 50, 59</i>
		<i>16, 18, 19, 21, 26</i>	\message		<i>21, 35</i>
\bibcop@verbose	..	<i>11, 27</i>	\month		<i>3</i>
\bibliography			N		
		<i>39, 40, 43, 44, 45</i>	\newcommand		<i>25</i>
\brackets		<i>3</i>	\no*		<i>2</i>
C			\number		<i>4</i>
\caps		<i>2</i>	P		
			\pages		<i>4</i>
			Y		
			\year		<i>3</i>
			\pgfkeys		<i>3</i>
			\proceedings		<i>4</i>
			\ProcessPgfPackageOptions		<i>14</i>
			R		
			\renewcommand		<i>45, 54</i>
			\RequirePackage		<i>1, 2, 23</i>
			S		
			\script		<i>2</i>
			\shorts		<i>3</i>
			\space		<i>26, 27,</i>
					<i>28, 29, 30, 31, 32, 33</i>
			T		
			\tags		<i>2</i>
			\types		<i>2</i>
			\typography		<i>4</i>
			U		
			\Unicode		<i>4</i>
			V		
			\verbose		<i>2</i>
			\volume		<i>4</i>